

CONiQ® Control 4.3" Compact

Weighing controller for industrial scales

- Intuitive touch controls
- Web-based user interface
- Modular design
- Simple system integration
- Legal-for-trade according to EN 45501



CONiQ Control 4.3" Compact is an innovative and flexible weighing control system for various industrial weighing applications and process controls. Awarded the reddot award 2019, the touch control interface intuitively guides the user through the program (according to ISO 9241) directly on the device or also using the web-based remote access.



Modular design

Configuration appropriate for your application.

- Functions determined by the software module used
- Three freely assignable slots for I/O expansion modules
- Color TFT touch display
- Connection of additional peripherals via USB
- No re-verification necessary when replacing mainboard or I/O modules
- Fieldbus interface for simple system integration
- Different enclosure variants

Award-winning user interface

- Intuitive handling
- Short learning time
- Clear text fault indication
- Three definable user groups

Web-based user interface

- No App or software installation required
- Browser-based
- Easy service access
- Remote support possible
- https encryption

Optional:



- WiFi for wireless service access
- Fieldbus card
- Memory expansion for recording process data



General data 4.3" Compact device




Display technology	4.3" color TFT with capacitive touch control
Display size (W x H)	95 x 53.7 mm
Power Supply	100 ... 240 VAC (-15%, +10%) Alternatively: 24 VDC (-7%, +12%)
Power consumption	Max. 30 W
Ambient temperature	Operation: -30 ... 50 °C Storage: -30 ... 80 °C
Date/time	Real-time clock, running time reserve without voltage: min. 7 days
Serial interfaces	1x RS485 (2-wire) and 1x RS232
Office bus interfaces	2x USB (master) 1x Ethernet (RJ45, 10/100BASE-T)
Fieldbus interface options (alternative)	Modbus-TCP Modbus-RTU PROFINET PROFIBUS DeviceNet EtherNet/IP
Slots for input/output modules	4 (1 occupied as standard for load cell interface)
Certifications	CE (EAC, UL, IECEx, ATEX in preparation) EU verification approval according to separate declaration of conformity

Control panel device



Operating panel cut-out (W x H)	282 ^{+0.5} x 88 ^{+0.5} mm
Protection class	Front: IP 65 Back: IP 20
Weight	1.4 kg

Wall & desktop device



Protection class	With membrane gaskets at rear: IP 54
Weight	2.3 kg


Input/output modules

Inputs and Outputs	Module
1 weighing circuit, 2 sensor inputs	VLC6033
6 binary inputs, 4 binary outputs (24 V, 0.5 A), 1 analog output 20mA	VBY6030
4 binary inputs, 2 binary outputs (24 V, 0.5 A)	VBY6032
8 relay outputs (230 VAC, 1 A)	VRY6030
3 analog outputs, 2 analog inputs; (each 20 mA or 10 V)	VAN6030
1 analog output, 1 analog input; (each 20 mA or 10 V)	VAN6031

Optional process communication

Interface/protocol	Module
Modbus TCP or Modbus RTU	Plug connection on basis module
PROFIBUS	VPB6030
PROFINET	VET6030
EtherNet/IP	VET6030
DeviceNet	VDN6030

Type code



www.schenckprocess.com/contact